



T-Max Tile_R Series

Solar roofing system

- Solar Roof Tile as the New Type of Building Materials Provide Green Energy for You
- One-Stop Solution Home Usings, Roof Tile and Solar Energy Intergrate Design



Innovative

Cloud shape | High compression resistance | Same life span as the building



Widely Used

Facade and rooftop solution | Increasing electricity generation



Waterproof Structure

Triple Waterproof Structure | GB/T 36584-2018 5.1



Fashion & Beauty

Integrated design | Beautiful

T-Max Tile_R Series

PHYSICAL PARAMETERS

Product model	JS55DG-8e 1/2
Dimensions	935*944mm
Weight	10.5kg
Glass (material/thickness)	Tempered glass/3.2mm+3.2mm
Cell	182*91mm
Junction box	≥IP67
Cable type	500mm / 4mm ²
Plug connector	MC4
Life span	>30years

ELECTRICAL PARAMETERS(STC)

Solar cells	Monocrystalline
Power output (P_{max})	55W
Module efficiency (%)	15.4%
Voltage at Pmax (V_{mpp})	8.90V
Current at Pmax (I_{mpp})	6.18A
Open-circuit current (V_{oc})	10.59V
Short-circuit current (I_{sc})	6.54A

STC: 1000W/m² irradiance , 25 degree cell temperature, AM1.5g.

PERFORMANCE GRADE

Color	Black
Load grade	2400Pa
Fireproofing grade	ClassA
Anti-hail grade	Φ25mm/23m/s
Operating temperature	-40°C~+85°C
Operating humidity	0-80%

OPERATING CONDITIONS

Max. system voltage	1500V _{DC}
Max. series fuse rating	20A
Operating temperature range	-40°C~+85°C
Max. static load, front (e.g., snow)	5400Pa
Max. static load, back (e.g., wind)	2400Pa
Max. hailstone impact (diameter / velocity)	25mm / 23m/s

THERMAL CHARACTERISTICS

Nominal operating cell temperature	NOCT	°C	45 ± 2
Temperature coefficient of P_{max}	γ	%/°C	-0.36
Temperature coefficient of V_{oc}	β_{Voc}	%/°C	-0.30
Temperature coefficient of I_{sc}	α_{Isc}	%/°C	0.05

Due to continuous innovation, research and product improvement, the specifications in this product information sheet are subject to change without prior notice. The specifications may deviate slightly and are not guaranteed.


The data do not refer to a single module and they are not part of the offer, they only serve for comparison to different module types.

QUALIFICATIONS AND CERTIFICATIONS

IEC 61215, IEC 61730, 3C, ISO 9001:2015, ISO 14001:2015, ISO 45001: 2018.

DIMENSIONS

Unit : mm



PRODUCT PICTURE



INSTALL



TikTok

Baoding Jiasheng Photovoltaic Technology Co., Ltd.

E-mail:commerce.gs@yingligroup.com

Hotline: +86-0312-7510221

Address: No. 88 Hengyuan West Road, Baoding

National High-tech Zone, Hebei Province, China

Web address: www.gainsolarbipv.com