JS360CB-120

PHYSICAL PARAMETERS			
Product model	JS360CB-120		
Size(Length*Width*Thickness)	1820*1451.1*8mm(Frameless)		
Weight	87kg		
Glass (material/thickness)	Tempered glass 3.2mm		
Junction box	IP68		
Cable type	4mm²		
Plug connector	18-01 Baoding Yitong PV Science & Technology Co., Ltd.		
Fire resistance class	ClassA		

ELECTRICAL PARAMETERS(STC)	
Power output (P _{max})	360W±3%
Module Efficiency STC(%)	13.63%
Power tolerance	0 ~+5W
Voltage at Pmax (V _{mpp})	68.33V
Current at Pmax (I _{mpp})	5.27A
Open circuit voltage(V _c)	81.26 V (±3%)
Short-circuit current (I _{sc})	5.66 A (±3%)
Maximum system voltage	DC 1500V
Maximum Over-Current Protection Rating [A]	30A

STC: 1000W/m² irradiance , 25°C cell temperature, AM1.5. (Made in China)

LIMITED POWER WARRANTY	
1st year degradation	≤1%
30th year degradation	≤12%
Linear power warranty	30 years
Limited product warranty	15 years


TEMPERATURE COEFFICIENT			
Temperature coefficients of P _{max}	γ	%/°C	-0.32%/°C
Temperature coefficients of V _{oc}	β_{Voc}	%/°C	-0.25%/°C
Temperature coefficients of Isc	$\boldsymbol{\alpha}_{lsc}$	%/°C	+0.055%/°C

PRODUCT PICTURE



DIMENSIONS

Unit:mm



Due to continuous innovation, research and product improvement, the specifications in this product information sheet are subject to change without prior notice. The specifications may deviate slightly and are not guaranteed. The data do not refer to a single module and they are not part of the offer, they only serve for comparison to different module types.



Baoding Jiasheng Photovoltaic Technology Co., Ltd.

E-mail:commerce.gs@yingligroup.com

Hotline:+86-0312-7510221

Address: Baoding Jiasheng Photovoltaic Technology Co., Ltd.

No.416, 4 Floor, A Zone Building No.88 West Hengyuan Street071000 Baoding, Hebei PEOPLE'S REPUBLIC OF CHINA

Web address: www.gainsolarbipv.com



f o gainsolar2007



Gain Solar



Gainsolar1