JS335CB-108P

PHYSICAL PARAMETERS			
Product model	JS335CB-108P		
Size(Length*Width*Thickness)	1729.2*1450*8mm(Frameless)		
Weight	35kg		
Glass (material/thickness)	Tempered glass 3.2mm		
Junction box	IP68		
Cable type	4mm²		
Plug connector	18-01 Baoding Yitong PV Science & Technology Co., Ltd.		
Fire resistance class	ClassA		

ELECTRICAL PARAMETERS(STC)				
Power output (P _{max})	335W±3%			
Module Efficiency STC(%)	13.36%			
Power tolerance	0 ~ +5W			
Voltage at Pmax (V _{mpp})	30.51V			
Current at Pmax (I _{mpp})	10.98A			
Open circuit voltage(V_c)	36.02V(±3%)			
Short-circuit current (I _{sc})	11.78A(±3%)			
Maximum system voltage	DC 1500V			
Maximum Over-Current Protection Rating [A]	30A			
STC: 1000W/m² irradiance , 25°C cell temperature, AM1.5.				

LIMITED POWER WARRANTY		
1st year degradation	≤1%	
30th year degradation	≤12%	
Linear power warranty	30 years	
Limited product warranty	15 years	


TEMPERATURE COEFFICIENT					
Temperature coefficients of P _{max}	γ	%/°C	-0.32%/°C		
Temperature coefficients of Voc	β_{Voc}	%/°C	-0.25%/°C		
Temperature coefficients of Isc	$\boldsymbol{\alpha}_{lsc}$	%/°C	+0.055%/°C		

PRODUCT PICTURE



DIMENSIONS

Unit:mm



Due to continuous innovation, research and product improvement, the specifications in this product information sheet are subject to change without prior notice. The specifications may deviate slightly and are not guaranteed. The data do not refer to a single module and they are not part of the offer, they only serve for comparison to different module types.



(Made in China)

Baoding Jiasheng Photovoltaic Technology Co., Ltd.

E-mail:commerce.gs@yingligroup.com

Hotline:+86-0312-7510221

Address: Baoding Jiasheng Photovoltaic Technology Co., Ltd.

No.416, 4 Floor, A Zone Building No.88 West Hengyuan Street071000 Baoding, Hebei PE \mathbf{OPLE} 'S REPUBLIC \mathbf{OF} CHINA

Web address: www.gainsolarbipv.com





Gain Solar

