## JS225CB-72

PHYSICAL PARAMETERS				
Product model	JS225CB-72			
Size(Length*Width*Thickness)	1450*1173*8mm(Frameless)			
Weight	56kg			
Glass (material/thickness)	Tempered glass 3.2mm			
Junction box	IP68			
Cable type	4mm²			
Plug connector	18-01 Baoding Yitong PV Science & Technology Co., Ltd.			
Fire resistance class	ClassA			

ELECTRICAL PARAMETERS(STC)		
Power output ( P <sub>max</sub> )	225W±3%	
Module Efficiency STC(%)	13.23%	
Power tolerance	0~ +5W	
Voltage at Pmax (V <sub>mpp</sub> )	41.23V	
Current at Pmax (I <sub>mpp</sub> )	5.46A	
Open circuit voltage( $V_{oc}$ )	48.81 V (±3%)	
Short-circuit current ( $I_{sc}$ )	5.85 A (±3%)	
Maximum system voltage	DC 1500V	
Maximum Over-Current Protection Rating [A]	30A	

STC: 1000W/m<sup>2</sup> irradiance, 25°C cell temperature, AM1.5. (Made in China)

LIMITED POWER WARRANTY	
1st year degradation	≤1%
30th year degradation	≤12%
Linear power warranty	30 years
Limited product warranty	15 years


TEMPERATURE COEFFICIENT					
Temperature coefficients of P <sub>max</sub>	γ	%/°C	-0.32%/°C		
Temperature coefficients of Voc	$\beta_{\text{voc}}$	%/°C	-0.25%/°C		
Temperature coefficients of I <sub>sc</sub>	$\boldsymbol{\alpha}_{lsc}$	%/°C	+0.055%/°C		

## PRODUCT PICTURE



## **DIMENSIONS**

Unit:mm



Due to continuous innovation, research and product improvement, the specifications in this product information sheet are subject to change without prior notice. The specifications may deviate slightly and are not guaranteed. The data do not refer to a single module and they are not part of the offer, they only serve for comparison to different module types.



## Baoding Jiasheng Photovoltaic Technology Co., Ltd.

E-mail:commerce.gs@yingligroup.com

Hotline:+86-0312-7510221

Address: Baoding Jiasheng Photovoltaic Technology Co., Ltd.

No.416, 4 Floor, A Zone Building No.88 West Hengyuan Street071000 Baoding, Hebei PEOPLE'S REPUBLIC OF CHINA

Web address: www.gainsolarbipv.com





Gain Solar



Gainsolar1